

Product Information

AVENO Mineral 10W-40

0002-000011



Description

AVENO Mineral 10W-40 is a mineral engine oil for petrol and diesel car engines with or without turbocharging and direct injection. Extended oil change intervals as per manufacturer's instructions. With AVENO Mineral 10W-40, a reliable and heavy-duty engine oil has been developed.

Instructions for use

AVENO Mineral 10W-40 is an engine oil for year-round use, and is ideal for all modern petrol and diesel car engines. AVENO Mineral 10W-40 can be used in engines with the specifications indicated. The operating instructions of the car and engine manufacturers must be observed.

Quality classification

Specification

- API SF/CD

Properties

- Excellent cold starting properties
- Fuel savings under all operating conditions
- Neutrality towards sealants
- Low evaporation, thus low oil consumption
- Suitable for catalytic converters
- A very stable and excellent viscosity behavior and shear stability
- Very good detergent and dispersing properties
- Extensive protection against wear, corrosion and foaming
- Extended oil change intervals protect natural resources

Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	99,0	mm ² /s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	14,5	mm ² /s	DIN 51659-2:2017-02
Viscosity Index	151		DIN ISO 2909:2004-08
Appearance	YELLOWBROWN		VISUELL
Viscosity CCS at -25°C	5940	mpa*s	ASTM D 5293:2020
Density at 15°C	859	kg/m ³	DIN EN ISO 12185:1997-11
Pour Point	-36	°C	ASTM D 7346:2015
Total Base Number (TBN)	5,2	mgkoh/g	ASTM D 2896:2015