Product Information

AVENO FS Excellence FD 5W-30

0002-000039



Description

AVENO FS Excellence FD 5W-30 is a synthetic smooth-running engine oil for petrol and diesel car engines with or without turbocharging and direct injection. AVENO FS Excellence FD 5W-30 is characterized by its excellent cold starting properties, minimization of fuel consumption, friction and wear. Extended oil change intervals as per manufacturer's instructions. AVENO FS Excellence FD 5W-30 is an engine oil specifically for the requirements of Ford and Renault.

Instructions for use

AVENO FS Excellence FD 5W-30 is an energy-efficient engine oil for year-round use, and is ideal for modern petrol and diesel car engines. AVENO FS Excellence FD 5W-30 can be used in Ford and Renault engines with the specifications indicated. The operating instructions of the automobile and engine manufacturer must be observed.

Quality classification		
Specification		
• ACEA A1/B1 • ACEA A5/B5	• API SL/CF	
Approval		
API SL Renault RN700	• Ford WSS-M2C913-D	
Recommendation		
Fiat 9.55535-N1Ford WSS-M2C913-A/B/C	Iveco 18-1811 Classe S1/S2Jaguar Land Rover STJLR.03.5003	
Properties		

- Fuel savings under all operating conditions
- Neutrality towards sealants
- · Low evaporation, thus low oil consumption
- Extended oil change intervals protect natural resources
- Excellent cold starting properties, even at low temperatures
- Very good detergent and dispersing properties
- Extensive protection against wear, corrosion and foaming

Technical specifications				
Properties	Data	Unit	Testing under	
Kinematic Viscosity at 40°C	58,5	mm²/s	DIN 51659-2:2017-02	
Kinematic Viscosity at 100°C	10,1	mm²/s	DIN 51659-2:2017-02	
Viscosity Index	162		DIN ISO 2909:2004-08	
Appearance	YELLOWBROWN		VISUELL	
Viscosity CCS at -30°C	4800	mpa*s	ASTM D 5293:2020	
Density at 15°C	851	kg/m³	DIN EN ISO 12185:1997-11	
Pour Point	-39	°C	ASTM D 7346:2015	
Total Base Number (TBN)	10,0	mgkoh/g	ASTM D 2896:2015	