

# Product Information

## AVENO TO-4 SAE 30

0002-000119



### Description

AVENO TO-4 SAE 30 is a special transmission oil for supplying construction machinery and tractors. AVENO TO-4 SAE 30 meets the increased demands of the Caterpillar TO-4 specification and is therefore suitable for use in gearboxes, end drives, hydraulic systems, wet brakes and clutches which require this specification.

### Instructions for use

AVENO TO-4 SAE 30 ensures maximum wear protection in various gearboxes, such as side drives and differentials, it optimizes the friction coefficient in power-shift transmissions, wet brakes and clutches and guarantees maximum service life for the units.

### Quality classification

#### Specification

- API CF
- API MT-1

#### Recommendation

- Allison C-4
- Caterpillar TO-4M/FD-1
- Komatsu KES 07.868.1
- ZF TE-ML 03C/07F

### Properties

- A high dispersion and detergent capability
- High oxidation stability
- A high and stable viscosity index
- Outstanding high-pressure properties
- Protection against wear, corrosion and foaming

### Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	96,2	mm <sup>2</sup> /s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	11,6	mm <sup>2</sup> /s	DIN 51659-2:2017-02
Viscosity Index	110		DIN ISO 2909:2004-08
Appearance	BROWN		VISUELL
Density at 15°C	883	kg/m <sup>3</sup>	DIN EN ISO 12185:1997-11
Pour Point	-33	°C	ASTM D 7346:2015