Product Information

AVENO TO-4 SAE 60

0002-000121



Description

AVENO TO-4 SAE 60 is a special transmission oil for supplying construction machinery and tractors. AVENO TO-4 SAE 60 meets the increased demands of the Caterpillar TO-4 specification and is therefore suitable for use in gearboxes, final dives, hydraulic systems, wet brakes and clutches which require this specification.

Instructions for use

AVENO TO-4 SAE 60 ensures maximum wear protection in various gearboxes, such as side drives and differentials, it optimizes the friction coefficient in power-shift transmissions, wet brakes and clutches and guarantees maximum service life for the units.

Quality classification			
Specification			
• API CF		• API MT-1	
Recommendation			
• Allison C-4		• Komatsu KES 07.868.1	
• Caterpillar TO-4M/FD-1		• ZF TE-ML 03C	
Properties			
A high dispersion and detergent capability		Outstanding high-pressure properties	
High oxidation stability		 Protection against wear, corrosion and foaming 	
• A high and stable viscosity index			
Technical specifications			
Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	312,6	mm²/s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	23,5	mm²/s	DIN 51659-2:2017-02
Viscosity Index	95		DIN ISO 2909:2004-08
Appearance	YELLOWBROWN		VISUELL
Density at 15°C	903	kg/m³	DIN EN ISO 12185:1997-11
Pour Point	-12	°C	ASTM D 7346:2015
Total Base Number (TBN)	9,2	mgkoh/g	ASTM D 2896:2015

Deutsche Ölwerke Lubmin GmbH | Freesendorfer Weg 4 | 17509 Lubmin | Phone +49 38354 / 179530 | Fax +49 38354 / 179579

Notice: To the best of our knowledge, all of the information provided was in accordance with the latest findings and developments of the Deutsche Ölwerke Lubmin GmbH. Our products are subject to continuous development. For this reason, our products, the manufacturing processes and all related information on this product page are subject to change at any time and without notice, unless customer-specific agreements exist. The data listed are based on standardized test procedures under appropriate laboratory conditions and are to be regarded as general, non-binding reference values.