## **Product Information**

### **AVENO Semi Synth. 2-stroke engine RED**

0002-000142



#### Description

AVENO Semi Synth. 2-stroke engine RED is high quality semi synthetic two-stroke engine oil, suitable for air -and water-cooled 2-stroke engines as well as for separate lubrication systems and self-mixing systems. AVENO Semi Synth. 2-stroke engine RED was developed based on synthetic base oils with effectively low ash additives for optimum protection against wear and prevent corrosion, deposits and auto-ignitions, even with heavy loads.

#### Instructions for use

AVENO Semi Synth. 2-stroke engine RED can generally be mixed with regular petrol 1:75 (regulations of engine manufacturers must be observed). It is a "self-mixing" two-stroke engines oil, suitable for separate lubrication systems and self-mixing systems. AVENO Semi Synth. 2-stroke engine RED is especially designed for the lubrication of air-cooled two-stroke petrol engines with high speed and heavy load. AVENO Semi Synth. 2-stroke engine RED is also suitable for the lubrication of two stroke petrol engines with water cooling (e.g. in motorbikes).

# Quality classification Specification • API TC • ISO-L-EGD • JASO FD

#### **Properties**

- Low exhaust emission levels
- Clean spark plugs provide optimal performance of the engines
- A proper lubrication of all engine parts

- · A very high wear and corrosion protection
- A strong cleaning effect for combustion chambers
- Cleans intake and exhaust ports from combustion residues and deposits

Technical specifications			
Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	67,9	mm²/s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	9,7	mm²/s	DIN 51659-2:2017-02
Viscosity Index	123		DIN ISO 2909:2004-08
Appearance	ORANGE		VISUELL
Density at 15°C	868	kg/m³	DIN EN ISO 12185:1997-11
Pour Point	-36	°C	ASTM D 7346:2015