# **Product Information**

## **AVENO FS Racing 10W-50**

0002-000150



#### Description

AVENO FS Racing 10W-50 is a high-alloyed, synthetic, smooth-running, multi-grade engine oil with specially selected base oils. Thanks to its special additives, AVENO FS Racing 10W-50 is also suitable for an extremely sporting driving style. AVENO FS Racing 10W-50 is ideally suited to modern petrol engines under the heaviest of loads during car racing. AVENO FS Racing 10W-50 ensures an optimal lubrication layer, even at very high operating temperatures.

#### Instructions for use

AVENO FS Racing 10W-50 can be used as a special oil for car racing, even under the harshest of conditions.

Quality classification		
Specification		
• API SN/CF	• ACEA A3/B4	
Recommendation		
• MB 229.1, MB 229.3	• VW 501 00/505 00	

### **Properties**

- Year-round use as a synthetic engine-oil
- Fuel savings due to reduced friction wear
- Continuous high oil pressure
- Extensive protection against wear, corrosion and foaming
- Black sludge is prevented from forming

- A very stable and excellent viscosity behavior and shear stability
- High oil film stability to prevent wear
- Low evaporation, thus low oil consumption
- Suitable for catalytic converters
- Extended oil change intervals protect natural resources

Technical specifications Technical specifications				
Properties	Data	Unit	Testing under	
Kinematic Viscosity at 40°C	115,9	mm²/s	DIN 51659-2:2017-02	
Kinematic Viscosity at 100°C	17,4	mm²/s	DIN 51659-2:2017-02	
Viscosity Index	165		DIN ISO 2909:2004-08	
Appearance	YELLOWBROWN		VISUELL	
Viscosity CCS at -25°C	5580	mpa*s	ASTM D 5293:2020	
Density at 15°C	856	kg/m³	DIN EN ISO 12185:1997-11	
Pour Point	-36	°C	ASTM D 7346:2015	
Total Base Number (TBN)	10,2	mgkoh/g	ASTM D 2896:2015	