

Product Information

AVENO ATF DX VI COLORLESS

0002-000185



Description

AVENO ATF DX VI COLORLESS is an automatic gear oil on a basis of the latest technology of HC/HT hydrocrack oils, which is permitted by General Motors for use in vehicles with automatic gearboxes. The special formulation ensures a lifespan that is twice as long as that of a comparable ATF oil. AVENO ATF DX VI COLORLESS meets the requirements of the gear oil specifications of General Motors for all vehicles with hydramatic automatic gearboxes from 2006 onwards.

Instructions for use

AVENO ATF DX VI COLORLESS is fully backward compatible with DEXRON®-III (H), III and II E applications. Always follow the recommendations in your vehicle's instruction manual.

Quality classification

Specification

- GM Dexron® VI
- Aisin Warner AW-1

Recommendation

- ATF Type 3.0, ATF Type 3.1
- BMW/Mini ATF 3+
- Ford/Lincoln/Mercury XT-6-DSP [SP]
- Ford/Lincoln/Mercury XT-6-QSP [SP]
- Honda ATF DW-1
- Hyundai/Kia NWS 9638 T-5
- Jaguar C2C 8432
- Mazda FZ, Mazda FW 6A EL, Mazda FW 6AX EL
- MB 236.12, MB 236.14, MB 236.41
- Mitsubishi ATF-J3, Mitsubishi Diaqueen ATF-PA
- Nissan Matic-S
- Porsche 000 043 304 00
- Shell 3353/134/M-1375.4/12108
- SP-IV/SPH-IV/SP-IV-RR
- Toyota Scion FZ, Toyota WS
- VOLVO 97342 (AT 102)
- VW G 052 533, VW G 055 005 A/A2
- VW G 055 540 A2, VW G 060 162 A1/A2/A6
- ZF Lifeguardfluid 5/6

Properties

- Superior wear protection
- Better resistance to foaming for smooth switching
- Reduced wear of bearings, bushings and gears
- Longer change intervals
- Excellent fluidity at low temperatures
- Good resistance against lubricant failures under hard operating conditions
- Outstanding resistance to oil sludge and deposit formation
- Longer oil lifespan, extension of the gearbox lifespan
- Prevention of coupling grinding in modulation rotary converters

Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	29,1	mm ² /s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	6,0	mm ² /s	DIN 51659-2:2017-02
Viscosity Index	161		DIN ISO 2909:2004-08
Appearance	YELLOW		VISUELL
Density at 15°C	841	kg/m ³	DIN EN ISO 12185:1997-11
Pour Point	-48	°C	ASTM D 7346:2015