

# Product Information

## AVENO Gear Super Synth. 75W-80 GL-4

0002-000204



### Description

AVENO Gear Super Synth. 75W-80 GL-4 is a semi-synthetic gear oil especially for maximum-duty hypoid toothed gearboxes. AVENO Gear Super Synth. 75W-80 GL-4 is designed on a basis of high-quality solvent refined and synthetic base oils and specially coordinated additives with high-pressure (EP) active agents and other supplements. This ensures compliance with today's practical requirements is exceeded.

### Instructions for use

AVENO Gear Super Synth. 75W-80 GL-4 is a high-performance gear oil for use in maximum-duty hypoid toothed gearboxes (axle drives, manual gearboxes, etc.), where high-pressure gear oils are required.

### Quality classification

#### Specification

- API GL-4

#### Recommendation

- PSA Standard B 71 2315

### Properties

- A very good oxidation resistance
- A low pour point
- A high viscosity index
- Most extensive protection against rust formation, corrosion, foaming
- Excellent high-pressure (EP) properties
- Fuel savings

### Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	43,3	mm <sup>2</sup> /s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	8,5	mm <sup>2</sup> /s	DIN 51659-2:2017-02
Viscosity Index	177		DIN ISO 2909:2004-08
Appearance	LIGHT YELLOW		VISUELL
Density at 15°C	847	kg/m <sup>3</sup>	DIN EN ISO 12185:1997-11
Pour Point	-39	°C	ASTM D 7346:2015