

# Product Information

## AVENO Gear Super Synth. LX 75W-85 GL-5

0002-000216



### Description

AVENO Gear Super Synth. LX 75W-85 GL-5 is a synthetic rear axle transmission fluid for highly stressed transmissions. It was developed based on synthetic base oils with a special additive and inhibition for limited slip applications. AVENO Gear Super Synth. LX 75W-85 GL-5 is adapted to the increased stress on transmission fluids, to ensure the proper functioning of the transmission.

### Instructions for use

AVENO Gear Super Synth. LX 75W-85 GL-5 is specifically for the lubrication of transfer cases and differential gears with limited slip. AVENO Gear Super Synth. LX 75W-85 GL-5 was specifically developed for Toyota and Lexus. AVENO Gear Super Synth. LX 75W-85 GL-5 ensures the proper lubrication of transmissions. Please observe the operating instructions from the car and transmission manufacturers.

### Quality classification

#### Specification

- API GL-5
- API MT-1
- MIL-L-2105 E
- SAE J2360

#### Recommendation

- BMW 83 22 2 295 532
- Honda HGO-1 (08200-9014)
- MB 235.7, MB 239.71, MB 239.72, MB 235.74
- VW TL 521 45-X (G 052 145 A1)
- VW TL 521 90 (G 052 190 A2/ G 055 190 A2)
- ZF TE-ML 18

### Properties

- Excellent viscosity-temperature behavior
- Excellent extreme pressure properties
- Excellent limited slip properties
- Minimal wear
- Prevention of foam generation
- Neutral behavior towards metal and sealing materials

### Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	62,5	mm <sup>2</sup> /s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	11,3	mm <sup>2</sup> /s	DIN 51659-2:2017-02
Viscosity Index	176		DIN ISO 2909:2004-08
Appearance	LIGHT YELLOW		VISUELL
Density at 15°C	865	kg/m <sup>3</sup>	DIN EN ISO 12185:1997-11
Pour Point	-51	°C	ASTM D 7346:2015