

# Product Information

## AVENO Circulating Oil CL 150

0002-000272



### Description

AVENO Circulating Oil CL 150 is produced on a basis of high-quality mineral oils and proven additives. Thanks to its special combination of active ingredients, it is suitable for use as a simple machine lubricant where no EP-additive oils are required.

### Instructions for use

AVENO Circulating Oil CL 150 has very good properties as a lubricant. Therefore AVENO Circulating Oil CL 150 can preferably be used for industrial gears and circulation systems of low and medium loads, where lubricants are required in accordance with DIN 51517-2.

### Quality classification

#### Specification

- DIN 51517-2 (CL)

### Properties

- A good wear protection
- Prevents foam formation
- Good water separation characteristics
- A mild additive and is therefore particularly suitable for old machines
- Inhibits rust and corrosion and protects against ferrous metal corrosion

### Technical specifications

| Properties                   | Data   | Unit               | Testing under            |
|------------------------------|--------|--------------------|--------------------------|
| Kinematic Viscosity at 40°C  | 150,0  | mm <sup>2</sup> /s | DIN 51659-2:2017-02      |
| Kinematic Viscosity at 100°C | 14,8   | mm <sup>2</sup> /s | DIN 51659-2:2017-02      |
| Viscosity Index              | 98     |                    | DIN ISO 2909:2004-08     |
| Appearance                   | YELLOW |                    | VISUELL                  |
| Density at 15°C              | 885    | kg/m <sup>3</sup>  | DIN EN ISO 12185:1997-11 |
| Pour Point                   | -18    | °C                 | ASTM D 7346:2015         |