

# Product Information

## AVENO FS Dura Fusion 5W-40

0002-000333



### Description

AVENO FS Dura Fusion 5W-40 is a synthetic low SAPS engine oil for petrol and diesel engines. It is suitable for most modern diesel engines with particle filter. AVENO FS Dura Fusion 5W-40 is characterized by excellent cold-start properties, minimization of fuel consumption, friction and wear. It contributes to the protection of the environment. Extended oil change intervals according to Manufacturer's instructions.

### Instructions for use

AVENO FS Dura Fusion 5W-40 is a synthetic engine oil, which was developed especially for diesel engines with particle filter.

### Quality classification

#### Specification

- ACEA C4

#### Recommendation

- MB 226.51, MB 229.51
- Renault RN0720

### Properties

- Excellent cold-start properties even at low temperatures below -30°C
- Fuel saving under all operating conditions
- Neutrality to sealing materials
- Low evaporation tendency, thus low oil consumption
- Low SAPS = reduced sulphated ash, phosphorus and sulfur
- The function of the hydraulic tappets is guaranteed at all temperatures
- A safe lubricating film at high operating temperatures
- An extensive protection against wear, corrosion and foaming
- Extended oil change intervals protect natural resources

### Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	45,8	mm <sup>2</sup> /s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	6,8	mm <sup>2</sup> /s	DIN 51659-2:2017-02
Viscosity Index	99		DIN ISO 2909:2004-08
Appearance	YELLOW		VISUELL
Density at 15°C	876	kg/m <sup>3</sup>	DIN EN ISO 12185:1997-11
Pour Point	-27	°C	ASTM D 7346:2015