

Product Information

AVENO FS 2-stroke engine RED

0002-000369



Description

AVENO FS 2-stroke engine is recommended for the lubrication of air-cooled 2-stroke petrol engines with high speeds and under the heaviest loads as well as for the lubrication of separate lubrication and self-mixing systems. AVENO FS 2-stroke engine is suitable for high-quality, high-speed units such as brush cutters, leaf blowers, etc. with over 6,000 rpm. AVENO FS 2-stroke engine is a synthetic 2-stroke oil based on synthetic base oils, selected 2-stroke additives and a proportion of PIB. It is characterized by high wear protection and reduced corrosion as well as prevention of deposits and glow ignitions. AVENO FS 2-stroke engine is ideally suited for air and water-cooled 2-stroke engines, as well as for separate lubrication and self-mixing systems.

Quality classification

Specification

- API TC
- ISO L-EGD
- JASO FD

Recommendation

- Husqvarna
- Piaggio Hexagon
- Rotax
- Stihl

Properties

- High cleaning effect
- Excellent lubrication of all engine parts
- High wear and corrosion protection
- Low exhaust emissions due to high combustion
- Keeps combustion chambers largely free of combustion residues and deposits
- Keeps intake and exhaust ports largely free of combustion residues and deposits
- Clean spark plugs ensure optimum engine performance

Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 40°C	67,9	mm ² /s	DIN ISO 51562-2:1988-12
kinematic viscosity at 100°C	10,6	mm ² /s	DIN ISO 51562-2:1988-12
viscosity index	144		DIN ISO 2909:2004-08
appearance	RED		VISUELL
density at 15°C	868	kg/m ³	DIN EN ISO 12185:1997-11
Pour Point	-39	celsius	ASTM D 7346:2015