# **Product Information**

## **AVENO Professional LongLife IV 0W-20**

0002-000509



#### Description

AVENO Professional Longlife IV 0W-20 was specially developed for the latest Volkswagen specification VW 508 00/509 00 (also known as VW Blue Oil). It combines longevity and protection in a low viscosity engine oil with lowered HTHS. Developed by experts to help extend the life and efficiency of the latest generation petrol and diesel vehicles requiring SAE 0W-20 viscosity grades. The specification ACEA A1/B1 is met, so AVENO Professional Longlife IV 0W-20 is of course also suitable for many vehicles from other manufacturers.

#### Instructions for use

AVENO Professional Longlife IV 0W-20 can only be used in modern engines and is not backward compatible. It is ideally suited for extended oil change interval (Longlife) applications where the use of SAE 0W-20 engine oil with reduced ash content and reduced HTHS is required. Distinguishing features such as a specific color and chemical markers are included. Observe manufacturer's instructions!

### **Quality classification**

#### **Specification**

• ACEA C5

### Recommendation

• Porsche C20

• FORD WSS-M2C956-A1

• VW 508 00/509 00

### **Properties**

- Future-proof additives for future engine generations
- Excellent motor protection
- Lowered HTHS viscosity for maximum fuel economy
- VW Blue Oil typical coloring to avoid confusion

- High fuel efficiency
- Excellent for prolonged maintenance intervals
- Highest oxidation stability based on fully synthetic PAO base oils
- Best cold start properties and by SAE class 0W-20

| Technical specifications     |       |         |                          |
|------------------------------|-------|---------|--------------------------|
| Properties                   | Data  | Unit    | Testing under            |
| Kinematic Viscosity at 40°C  | 39,2  | mm²/s   | DIN 51659-2:2017-02      |
| Kinematic Viscosity at 100°C | 8,0   | mm²/s   | DIN 51659-2:2017-02      |
| Viscosity Index              | 182   |         | DIN ISO 2909:2004-08     |
| Appearance                   | GREEN |         | VISUELL                  |
| Viscosity CCS at -35°C       | 3250  | mpa*s   | ASTM D 5293:2020         |
| Density at 15°C              | 836   | kg/m³   | DIN EN ISO 12185:1997-11 |
| Pour Point                   | -60   | °C      | ASTM D 7346:2015         |
| Total Base Number (TBN)      | 8,3   | mgkoh/g | ASTM D 2896:2015         |