

Product Information

AVENO Super Truck 60

0002-000535



Description

AVENO Super Truck 60 is an HD engine oil, high-alloyed with synthetic additives suitable for diesel lorry engines, including with turbo charging. With AVENO Super Truck 60 a reliable and heavy-duty engine oil has been developed.

Instructions for use

AVENO Super Truck Turbo 60 is an engine oil for year-round use, and is suitable for diesel engines and commercial vehicle engines with and without turbo charging. AVENO Super Truck Turbo 60 can be used in engines with the specifications indicated. The operating instructions of the engine manufacturer must be observed.

Quality classification

Specification

- API CF-4/SG
- MIL-L-2104 D
- Kinematic Viscosity at 40°C
- Kinematic Viscosity at 100°C
- Viscosity Index
- Density at 15°C
- Flash Point (COC)
- Infrared Spectrum
- Pour Point
- ACEA E2/B4
- Total Base Number (TBN)

Recommendation

- Allison C-4
- Caterpillar TO-2
- Deutz DQC I-02
- MB 228.0
- ZF TE-ML 04B/04E

Properties

- Neutrality towards sealants
- Suitable for catalytic converters
- A very good shear stability
- Prevention of black sludge formation
- A high oxidation stability
- A stable and excellent viscosity behavior
- Good detergent and dispersing properties
- Extensive protection against wear, corrosion and foaming
- High safety margin even in boundary lubrication