# **Product Information**

# **AVENO Excellence RN 5W-30**

0002-000688



#### Description

AVENO Excellence RN 5W-30 is a synthetic low-friction engine oil for passenger car gasoline and diesel engines. It is specifically geared towards the technical requirements of Renault car engines. The low-SAPS formulation helps to keep the particle filter clean and prevents the exhaust aftertreatment system from clogging.

#### Instructions for use

AVENO Excellence RN17 was specially developed for the technical requirements of RENAULT and DACIA vehicles. Other possible uses are gasoline engines with and without gasoline particulate filters (OPF), as well as diesel engines with and without DPF (diesel particulate filters), if an engine oil according to ACEA C3 is required. The Renault specification RN17 replaces the specification RN0700 and RN0710 and can be used for engines where these specifications are recommended.

### **Quality classification**

### **Specification**

• ACEA C3

#### Recommendation

• MB 226.52

• Renault RN17

## • Renault RN0700/RN0710

#### **Properties**

- Low content of ash-forming components (sulphated ash, phosphorus and sulfur)
- Specific additive technology for optimal lubrication

• Extremely high resistance to aging

• Excellent cleaning properties

Technical specifications			
Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	64,85	mm²/s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	12,22	mm²/s	DIN 51659-2:2017-02
Viscosity Index	189		DIN ISO 2909:2004-08
Appearance	YELLOWBROWN		VISUELL
Density at 15°C	848,4	kg/m³	DIN EN ISO 12185:1997-11
Pour Point	-33	°C	ASTM D 7346:2015